

Material Safety Data Sheet

Identity: **TRU BLEND with HydroStik**
Product: Wood / Paper fiber with tackifier

Date Revised: Feb. 9, 2009

SECTION I

Manufacturer/Supplier: Finn Corporation
9281 LeSaint Dr.
Fairfield, Ohio 45014
Tel: 513-874-2818 or 800-543-7166
Fax: 513-874-2914 Email: sales@finncorp.com

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Common Name	Percent	Exposure Limits
Wood dust	80 +/- 10	OSHA PEL-STEL: 10mg/m ³
CAS #	None	ACGIH TLV-TWA: 5mg/m ³
Paper	20 +/- 10	OSHA PEL=TWA..... 15mg/m ³
CAS #	9004-34-6	ACGIH TLV=TWA 5mg/m ³
Basic Green 4 and Acetic Acid	<1	OSHA PEL=TWA..... None
CAS #	569-64-2	ACGIH TLV=TWA None
Polysaccharide, Guar powdered tacifier	3	OSHA PEL=TWA..... None
CAS #	9000-30-0	ACGIH TLV=TWA None

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point (F).....	Not Applicable	Solubility in Water	Insoluble, Dispersible
Vapor Density.....	Not Applicable	Specific Gravity (H ₂ O=1)	0.015-0.025
Vapor Pressure (mm Hg)	Not Applicable	Appearance & Odor	Finely divided material
Melting Point	Not Applicable		Green in color
			Slight wood odor

SECTION IV – FIRE AND EXPLOSIVE HAZARD DATA

Flash Point..... >550F
Flammability Limits LEL

UEL	Not Applicable	See Unusual Fire and Explosion Hazards below.
-----------	----------------	---

Extinguishing Media

Special Fire Fighting Procedures	None
--	------

Unusual Fire and Explosion Hazards..... A concentration of 40,000 mg/m³ is often used as the lower explosive limit for wood dusts in the presence of a flame or spark. Limit depends on moisture content and particle diameter.
