



DESCRIPTION

FINN TRU-Max is a stabilized mulch matrix system designed especially for temporary, 3 to 6-month, soil stabilization and erosion control on construction areas where the soil has been disturbed. This FINN solution is easier and less expensive than other, labor-intensive, solutions.

FINN TRU-Max SMM consists of a proprietary, cross-linked, non-toxic tackifier blended with long-strand wood fibers from the forests of the Eastern United States. FINN TRU-Max is mixed in a HydroSeeder®, just like normal mulch products, and when applied creates a porous, erosion-resistant mat that protects the soil surface and holds it in place through re-wetting from repeated rains. FINN TRU-Max SMM:

- Retains integrity even after repeated rains
- Is perfect for construction sites and slopes where temporary erosion protection is required
- Is easier to apply and less expensive than alternative solutions
- Does not interfere with germination and growth
- High quality, produced under constant quality control checks from the finest American pines and poplars
- Shipped in easy to handle, quick-loading, specially designed UV-resistant 50-pound bags
- Includes non-toxic green dye to aid in even application and provide instant aesthetic appeal
- Non-toxic material decomposes over time and adds organic material to soil, aiding future revegetation

BASIC PRODUCT SPECIFICATIONS

Moisture Content:..... 12.0% plus/minus 3.0%
 Water holding capacity:..... min 1,250 gms. (per 100 grams oven dried fiber)
 Color:..... Green
 Compositon:..... Refined Wood Fiber (95% by total weight)
 Proprietary cross-linked binder (5% by total weight)
 See detailed MSDS materials for additional information

MANUFACTURING PROCESS

FINN TRU-Max SMM is manufactured to specific fiber sized in a temperature-controlled environment. Clean whole pine and poplar wood chips from the forests of the Eastern United States, are separated in a special defibration process, using steam, pressure, and rubbing action. This process turns the wood chips into fibers. Non-toxic green dye and a proprietary cross-linked, non-toxic tackifier are added. After going through a high-temperature drying and baking process, the finished mulch is bagged, weighed, and goes through rigorous sampling and quality control before shipment. This special process, using the finest raw materials and binders, creates a sterile, non-toxic SMM product brought to you from the inventor of the HydroSeeder®.

APPLICATION RATES AND PACKAGING

Packaging: FINN TRU-Max SMM is compressed and protected in UV-resistant 50 pound (22.7kg) easy to open and easy-loading bags, measuring 9 x 19 x 27 inches (23 x 48 x 69 cm). 40 bags are included in each stretch-wrapped pallet.

FINN recommends an application rate of 2,500 pounds/acre on flat to 3H:1V slopes; for slopes of 2.5H:1V, use 3,000 pounds per acre. For steeper slopes, contact FINN or your FINN dealer. Application should be done in two passes, from different directions if possible, to ensure needed consistency.



9281 LeSaint Drive
 Fairfield, OH 45014-5457
 Toll Free (800) 543-7166
 E-mail: sales@finncorp.com
 www.finncorp.com