



DESCRIPTION

FINN TRU-Wood is produced from the highest quality virgin poplar and pine wood chips for use in HydroSeeding® and erosion control applications. FINN Tru-Wood Mulch is:

- High quality wood mulch produced under constant quality control checks
- Produced from the finest American pines and poplars
- Consistent in fiber size and texture for optimum performance
- Shipped in easy to handle, quick-loading, specially designed UV-resistant 50-pound bags
- Perfect for mixing well into a homogenous slurry that will not dewater during difficult hose work
- Includes non-toxic green dye to aid in even application and provide instant aesthetic appeal

When FINN TRU-Wood is applied, the fibers twist and lock, forming a protective mulch mat to aid in erosion control, and holds seeds in place and aids germination in HydroSeeding®. FINN TRU-Wood Mulch is a superior product from the inventor of the HydroSeeder®

BASIC PRODUCT SPECIFICATIONS

Moisture Content:..... 12.0% plus/minus 3.0%
 Organic Matter:..... 99.3% plus/minus 0.2% (oven dried basis)
 Ash content:..... 0.7% plus/minus 0.2% (oven dried basis)
 pH @ 3% concentration:..... 4.8 plus/minus 0.5
 Water holding capacity:..... min 1,250 gms. (per 100 grams oven dried fiber)
 Color:..... Green
 Material Safety Data Class:.. Naturally Occurring Material
 See detailed MSDS materials for additional information

MANUFACTURING PROCESS

FINN TRU-Wood Mulch begins as clean whole pine and poplar wood chips from the forests of the Eastern United States. The wood fibers are separated in a special defibration process, using steam, pressure, and rubbing action. This process turns the wood chips into fibers. Non-toxic green dye is added, and the fibers go through a special treatment to increase water-holding capacity. After going through a high-temperature drying and baking process, the finished mulch is bagged, weighed, and goes through rigorous sampling and quality control before shipment.

This special FINN process, using the finest raw materials, creates a sterile, non-toxic HydroSeeding® and erosion control mulch of the highest quality, suitable to carry the FINN name.

APPLICATION RATES AND PACKAGING

Packaging: FINN TRU-Wood Mulch is compressed and protected in UV-resistant 50 pound (22.7kg) easy to open, easy-loading bags, measuring 9 x 19 x 27 inches (23 x 48 x 69 cm). 40 bags are included in each stretch-wrapped pallet.

FINN recommends a minimum application rate of 1,800 pounds/acre on flat to 5H:1V slopes; for 4H:1V slopes use a heavier application. For steeper slopes, consult FINN or your FINN dealer for advice on FINN Consumables that can be added to FINN TRU-Wood Mulch or other FINN mulches that are more suited to these conditions



9281 LeSaint Drive
 Fairfield, OH 45014-5457
 Toll Free (800) 543-7166
 E-mail: sales@finncorp.com
 www.finncorp.com